			plugin名

tooltip	1.
	`{!word:tooltip_text}}`
	2.
	`<ttip:style:marked_text> tooltip_text </ttip>`
		• style　　　　CSS
		　　 class
		`.tooltip_xxx`
			[tooltip](#)

	1.
	`<abbr>　 / 　 [　　　　 ]</abbr>`
	2.
	`<abbr>　　　( / 　 )</abbr>`
			[abbr](#)

	`<anno:1>　 / 　 </anno> <@anno:1>　　　 </@anno>`		[annotate](#)
	`<autott><content>　 / 　 </content><tip>` `　 </tip><title>　　　　 </title></autott>`		[autotooltip](#)
ruby	`{{ruby| 　 |ruby 　 }}`		[ruby](#)
anchor	anchor `{{anchor: _anchor_ 　 : 　　　　 }}`	# _anchor_ anchor　　　 　DokuWiki	[anchor](#)
	`|@< 　 >:< 　 >|`	• < 　 >　 #abcdef 　 HTML [1)](#) •	[cellbg](#)
caption	`[{{< 　　　　 >|<caption>}}]`	`{{…}}` 　 [　]	[imagebox](#)
	`{{page>xx:yy&...}}` 🔧Fix Me!	• 　　　　 flag 　 & • 　　　　 . .. • 　 #	[include](#)

			plugin

		Option	Description		
⬚popup⬚	`{{popup>%IMAGE/PAGE%?[%SIZE%]&[keepOpen]|[%TEXT/IMAGE%]}}`	%IMAGE/PAGE%	an image or a page as you know it from DokuWiki		popupviewer
		%SIZE% (optional)	Width and height (optional) in px. Example: 200×300		
		keepOpen (optional)	All links in a page opened via a popup will also open in a popup.		
		%TEXT/IMAGE% (optional)	Here you can set the name or an additional image. This will be displayed to the user as link to click on for the popup		

	`{{url>http(s)://... width,height noscroll noborder alignment|alternate-text}}`	✎**Fix Me!**⬚ • *width* and *height* are optional. When only one value is given it is assumed to be the height. Otherwise the first value is width and the second value is height. You can give the values in `px`, `em`, `pt` or `%`. When no unit is given `px` is̶ is NOT assumed (you have to give the value). Defaults values are: width - 98%, height - 400px. • `noscroll` will disable the scrollbars of the iframe • `noborder` will disable the frame border, note that your CSS might still add borders or may disable them without using this setting • Optionally an *alignment* can be given as `left` or `right` to have the iframe floating to the left or right. Should be used with a width. • An *alternate text* is optional. If not specified an empty string will be used.		iframe

Feed

			plugin⬚

feed plugin	`{{blogfeed>blog|Blog Entries}}`
	`{{blogfeed>blog?20|Blog Entries}}`
	
	`{{commentsfeed>mynamespace|Individual Comments}}`
	`{{commentsfeed>mynamespace?25|Individual Comments}}`
	
	`{{threadsfeed>namespace|Recent discussion threads}}`
	`{{threadsfeed>namespace?15|Recent discussion threads}}`
	
	`{{editorfeed>.?user|Pages edited by 'user'}}`
	
	`{{topicfeed>*?cloud|Tagged «Cloud»}}`
	
	`{{tasksfeed>projects|Open tasks}}`
	`{{tasksfeed>projects?overdue|Late tasks}}`
			feed

-

1)

From:
<http://ciangbrides.myds.me/dw/> - **Ciang Brides**

Permanent link:
http://ciangbrides.myds.me/dw/dokuwiki/syntax

Last update: **2019/04/03 10:19**